



## FOAM BUMPER PADS for HOTEL CARTS INSTALLATION INSTRUCTIONS

### *BOING 4000 - Instant Adhesive (Super Glue)*

Do not use *Silicone or other adhesives* - as they will not bond adequately



**Tools/Equipment:** Duct Tape + Cleaning Rag + Sandpaper + Sharp Knife + Solvent



**Warning: Do not glue your fingers together with the adhesive!!**



### Installation Slim "C" Corner Strips

#### Preparation


1. Lightly sand the existing hard rubber bumper to improve adhesion (remove any old or peeling paint)
2. Thoroughly clean the hard rubber bumper and metal frame with Solvent to remove all residue (including fingerprints). Let dry
3. Wipe the inside of the "C" shaped Foam Strip with Solvent to remove any residue. Let dry
4. OPTION: Notch Curved Corner Section



- where you have a sharp corner, you may need to notch the edges of the Slim "C" Strip where they go around the corner to prevent buckling
- we do not have "pre-formed" corners
- cutting these notches will help the strip lie down flatter around the curves

5. Apply very thin film of Boing 400 adhesive or SuperGlue to the inside of the Foam Strip

- **Do NOT put too much adhesive or it will not dry!!!!**
- Ensure the adhesive is also along outer edges.
- Start at one end of the strip near the middle of the cart.
- Apply adhesive to the first 6 inches - let it set (average one minute).
- After "anchoring" the first part of the strip continue with adhesive 12" at a time
- lift up and put back the strip to help spread the adhesive
- press down and hold to ensure proper bond



6. Continue the same way with the second Foam Strip starting from the same spot, but going in the opposite direction



7. Use "Duct Tape" as needed to temporarily hold the Foam Strips in place

- For larger c arts, there may be a small gap left over.
- Cut, and insert the "gap filler" strip into the space



8. After 5 minutes, carefully remove any duct tape
9. If you missed a spot you can go back and do touch-ups with the adhesive

**SOLVENT:** Mineral Spirits or Laquer Thinner or Acetone  
For "cured" adhesive, use a product such as Loctite X-MNS



**Other Padding products available** for different shaped carts

Quantity of these strips will depend on dimensions of cart




Follow the same "basic" installation instructions as above for the slim "C" strips



Slim V - 72"



Flat Pad - 39.4"



Basic Strip - 39.4"



3-D Jumbo Corner



2-D Jumbo Corner



2-D Mini



Air Corner

**CLEANING & MAINTENANCE:**

Use any general household cleaner + soft cloth

**Do not** use harsh abrasive scrubbing agents

**Do not** use strong chemicals like Citrus spray or Bleach

**Boing Safety**

136 Walker Street, Atlanta GA 30313

TEL 404-521-9054 ORDER: 800-477-6434 FAX: 404-222-8366

wwwBoingSafety.com info@BoingSafety.com