



INSTALLATION SILICONE vs. INSTANT ADHESIVE

Visit www.boingsafety.com for additional installation solutions for other products

There are thousands of different installation applications varying with surface materials (wood, metal, masonry, sheetrock, ceramic tile etc), textures (rough, smooth), temperature ranges, climatic conditions, moisture levels, etc..

In principle, each of these conditions requires a slightly different adhesive solution for maximum effectiveness.

We can only recommend adhesives that will work in “most”, but not necessarily, all cases.

Warranty will be voided if other non-approved adhesives are used.

A. Silicone

- best if you eventually want/need to remove our safety padding
- best for rough surfaces or where there are some thin “gaps” between our product and the surface
- 12-24 **hour** cure time
- available from most home builder/hardware/DIY suppliers
- you can download detailed instructions from our website www.boingsafety.com
- one tube can cover about 6 Basic Corner Strips
- use approved 100% silicone *GE Silicone, I or II or 2X* (Do not use DAP, Liquid Nails etc)



B. Instant Adhesive

- best when you want a really strong, permanent bond
- best for smooth/flat surfaces for maximum bond
- the bond is so strong that foam or rubber padding can actually rip when you try and remove
- no particularly good for bonding to some metals
- only 20 **second** wait time
- one 1oz bottle can cover about 5 Basic Corner Strips
- for small quantity use *Loctite Super Glue - Extra Time Control* (4gm) or similar off-the-shelf product
- for larger quantity: Use **BoingSafety 4000** (28.4gm or 57gm) We stock.



1. Preparation

- ensure that non-porous surfaces are clean and dry (painted or unpainted)
- clean areas with isopropyl (rubbing) alcohol wipes for best cleaning results
- for porous areas and outdoor areas subject to rain or moisture, first seal/waterproof surface with *Thompson Water Seal*

2. If required, cut or trim safety padding to size with a very sharp, thin blade knife.

3. Apply **Silicone** or **Instant Adhesive** as per manufacturer’s instructions

4. In outdoor or moist locations, seal any exposed interior foam with Silicone

SILICONE REMOVAL - use DAP “Silicone-Be-Gone” (see DAP website for store locations)

DAILY/WEEKLY CLEANING & MAINTENANCE:

Use any general household cleaner + soft cloth

Do not use harsh abrasive scrubbing agents

Do not use strong chemicals like Citrus spray or Bleach

Effective 15 August, 2011

Boing Safety
A Network USA Company

Atlanta GA 30313
TEL 404-521-9054 ORDER: 800-477-6434 FAX: 404-222-8366
wwwBoingSafety.com info@BoingSafety.com